



ESF-M1L57-A
Automotive Primary Wire
85°C

Features

Conductors available in tinned or copper
Insulation: 85°C PVC
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels or drums

Applications

Cables used for automotive electrical

<i>AWG size</i>	<i>Number of Strands</i>	<i>Strand Size (ga)</i>	<i>Nom Cond OD (in)</i>	<i>Nom OD (in)</i>	<i>Min Avg Wall (in)</i>	<i>Approx. Net Weight (lbs/mft)</i>	<i>Approx. Cu (lbs/mft)</i>
8	19	21	0.137	0.217	0.030	62	47
10	19	23	0.109	0.170	0.022	39	30
12	19	25	0.089	0.139	0.018	24	18
14	19	27	0.071	0.118	0.018	8	12
16	19	29	0.057	0.103	0.018	11	7
18	16	30	0.048	0.092	0.018	8	5
20	7	28	0.038	0.082	0.016	6	3

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.prestolitewire.com