



JASO type AVSS
Automotive Primary Wire
125°C

Features

Conductors available in tinned or copper
Insulation: 125°C XLPE
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels or drums

Applications

Cables used for automotive electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Min Avg Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
.5mm ²	7	.32mm	0.035	0.083	0.016	6	3
.75mm ²	41	.16mm	0.047	0.091	0.014	8	5
.85mm ²	11	.32mm	0.048	0.087	0.014	8	5
1.25mm ²	37	.21mm	0.055	0.108	0.019	12	8
2.0mm ²	37	.26mm	0.072	0.122	0.019	17	12
3.0mm ²	41	.32mm	0.095	0.158	0.022	28	20
5.0mm ²	65	.32mm	0.117	0.19	0.026	43	32
8.0mm ²	50	.45mm	0.159	0.221	0.028	64	49

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450
Phone: 800-952-3842 870-236-8141
Fax: 870-239-6139
Web: www.prestolitewire.com