



JASO type AV
Automotive Primary Wire
105°C

Features

Conductors available in tinned or copper
Insulation: 105°C PVC
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels or drums

Applications

Cables used for automotive electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Min Avg Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
.5mm ²	7	.32mm	0.035	0.091	0.019	7	3
.85mm ²	11	.32mm	0.048	0.098	0.019	9	5
1.25mm ²	16	.32mm	0.058	0.124	0.017	13	8
2mm ²	26	.32mm	0.058	0.124	0.017	18	13
5mm ²	65	.32mm	0.117	0.185	0.022	42	32
10mm ²	63	.45mm	0.195	0.264	0.039	81	60
15mm ²	171	.32mm	0.240	0.307	0.043	110	82

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.prestolitewire.com