



---

**JASO type AVSS**  
**Automotive Primary Wire**  
105°C

---

**Features**

Conductors available in tinned or copper  
Insulation: 105°C PVC  
RoHS and REACH Compliant

**Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors for base and stripe combinations  
Packaging options: reels or drums

**Applications**

Cables used for automotive electrical

<b>AWG size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (in)</b>	<b>Nom OD (in)</b>	<b>Min Avg Wall (in)</b>	<b>Approx. Net Weight (lbs/mft)</b>	<b>Approx. Cu (lbs/mft)</b>
.3mm <sup>2</sup>	7	.25mm	0.031	0.055	0.01	3	2
.5mm <sup>2</sup>	7	.32mm	0.037	0.063	0.01	5	3
.85mm <sup>2</sup>	11	.32mm	0.048	0.073	0.011	7	5
1.25mm <sup>2</sup>	19	.29mm	0.058	0.085	0.01	10	8
2.0mm <sup>2</sup>	37	.26mm	0.072	0.104	0.012	15	12

***Customer Service Group***

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.prestolitewire.com](http://www.prestolitewire.com)