



---

**JASO type CAVS**  
**Automotive Primary Wire**  
105°C

---

**Features**

Conductors available in tinned or copper  
Insulation: 105°C PVC  
RoHS and REACH Compliant

**Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors for base and stripe combinations  
Packaging options: reels or drums

**Applications**

Cables used for automotive electrical

<b>AWG size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (in)</b>	<b>Nom OD (in)</b>	<b>Min Avg Wall (in)</b>	<b>Approx. Net Weight (lbs/mft)</b>	<b>Approx. Cu (lbs/mft)</b>
.3mm <sup>2</sup>	7	.26mm	0.031	0.056	0.011	3	2
.5mm <sup>2</sup>	7	.32mm	0.035	0.063	0.011	5	3
.85mm <sup>2</sup>	11	.32mm	0.048	0.072	0.011	7	5
1.25mm <sup>2</sup>	16	.32mm	0.058	0.083	0.011	10	8

**Customer Service Group**

1 Prestolite Drive Paragould, Arkansas 72450  
Phone: 800-952-3842 870-236-8141  
Fax: 870-239-6139  
Web: [www.prestolitewire.com](http://www.prestolitewire.com)