



**SAE J1128 TXL**  
**Automotive Primary Wire**  
125°C

**Features**

Conductors available in tinned or copper  
Insulation: 125°C XLPE  
RoHS and REACH Compliant

**Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors for base and stripe combinations  
Packaging options: reels or drums

**Compliances**

Ford ESB-M1L123-A  
Ford ESB-M1I123-A2  
Chrysler MS-8288

**Applications**

Cables used for automotive electrical

<b>AWG size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (in)</b>	<b>Nom OD (in)</b>	<b>Min Avg Wall (in)</b>	<b>Approx. Net Weight (lbs/mft)</b>	<b>Approx. Cu (lbs/mft)</b>
22	7	30	0.030	0.062	0.013	4	48
20	7	28	0.038	0.07	0.013	5	30
18	16	30	0.048	0.082	0.013	7	19
18	19	31	0.045	0.078	0.013	7	12
16	19	29	0.056	0.088	0.013	10	7
14	19	27	0.069	0.103	0.013	15	5
12	19	25	0.088	0.128	0.013	23	5
10	19	23	0.108	0.155	0.017	37	3
8	19	21	0.137	0.191	0.018	57	2

***Customer Service Group***

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.prestolitewire.com](http://www.prestolitewire.com)