



---

## UL 62 TYPE SJOOW

### Multi-Conductor Cable

90°C DRY / 60°C WET

---

#### **Features**

Conductors available in tinned or copper  
Insulation: 105°C CPE

#### **Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors for base  
Packaging: reels

#### **Compliances**

RoHS and REACH Compliant  
Voltage Rating: 300 Volts

#### **Applications**

Cables used for flexible power cords

<b>AWG Size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (in)</b>	<b>Number Primary Conductors</b>	<b>Nom Jack OD (in)</b>	<b>Min Avg Wall (in)</b>	<b>Nom Jacket OD (in)</b>	<b>Jacket Min Avg wall (in)</b>	<b>Approx. Net Weight (lbs/Mft)</b>	<b>Approx. Cu (lbs/Mft)</b>
18	16	30	0.048	2	0.109	0.027	0.297	0.024	51	10
18	41	34	0.047	2	0.113	0.027	0.313	0.024	64	10
18	41	34	0.047	3	0.113	0.027	0.370	0.024	59	15
16	26	30	0.061	2	0.120	0.027	0.330	0.033	61	16
16	65	34	0.060	2	0.126	0.027	0.321	0.027	67	16
16	26	30	0.061	3	0.120	0.027	0.330	0.024	70	24
14	105	34	0.074	2	0.141	0.027	0.345	0.024	84	26
14	41	30	0.076	2	0.136	0.027	0.340	0.030	78	26
14	105	34	0.074	3	0.136	0.027	0.380	0.037	95	38
14	41	30	0.076	3	0.136	0.027	0.365	0.030	93	39
12	168	34	0.106	2	0.165	0.027	0.425	0.036	137	42
12	65	30	0.092	2	0.167	0.027	0.420	0.036	106	40

#### ***Customer Service Group***

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.prestolitewire.com](http://www.prestolitewire.com)