



UL 62 TYPE SJTOW

Multi-Conductor Cable

90°C DRY / 60°C WET

Features

Conductors available in tinned or copper
 Insulation: 105°C CPE

Compliances

RoHS and REACH Compliant
 Voltage Rating: 300 Volts

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors
 Packaging: reels

Applications

Cables used for flexible power cords

AWG Size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Number Primary Conductors	Nom Jack OD (in)	Min Avg Wall (in)	Nom Jacket OD (in)	Jacket Min Avg wall (in)	Approx. Net Weight (lbs/Mft)	Approx. Cu (lbs/Mft)
18	16	30	0.048	2	0.109	0.027	0.297	0.024	51	10
18	41	34	0.047	2	0.113	0.027	0.313	0.024	64	10
18	41	34	0.047	3	0.113	0.027	0.370	0.024	59	15
16	26	30	0.061	2	0.120	0.027	0.330	0.033	61	16
16	65	34	0.060	2	0.126	0.027	0.321	0.027	67	16
16	26	30	0.061	3	0.120	0.027	0.330	0.024	70	24
14	105	34	0.074	2	0.141	0.027	0.345	0.024	84	26
14	41	30	0.076	2	0.136	0.027	0.340	0.030	78	26
14	105	34	0.074	3	0.136	0.027	0.380	0.037	95	38
14	41	30	0.076	3	0.136	0.027	0.365	0.030	93	39
12	168	34	0.106	2	0.165	0.027	0.425	0.036	137	42
12	65	30	0.092	2	0.167	0.027	0.420	0.036	106	40

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.prestolitewire.com