



---

**UL 62 TYPE SO**  
**Multi-Conductor Cable**  
**90°C DRY / 60°C WET**

---

**Features**

Conductors available in tinned or copper  
Insulation: 105°C CPE

**Compliances**

RoHS and REACH Compliant  
Voltage Rating: 300 Volts

**Product Design Options**

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors  
Packaging: reels

**Applications**

Cables used for flexible power cords

<b>AWG Size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (in)</b>	<b>Number Primary Conductors</b>	<b>Nom Jack OD (in)</b>	<b>Min Avg Wall (in)</b>	<b>Nom Jacket OD (in)</b>	<b>Jacket Min Avg wall (in)</b>	<b>Approx. Net Weight (lbs/Mft)</b>	<b>Approx. Cu (lbs/Mft)</b>
14	41	30	0.076	2	0.181	0.040	0.531	0.08	150	26

***Customer Service Group***

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.prestolitewire.com](http://www.prestolitewire.com)