

UL Style 1230

Appliance Wiring

105°C - 600 volts AC - Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
 Insulation: 105°C PVC
 RoHS and REACH Compliant

Compliances

CSA TEW
 Voltage Rating 600 volts AC
 Horizontal Flame per UL 1581
 UL 758

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors for base and stripe combinations
 Packaging options: reels, drums, returnable containers

Applications

Internal wiring

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
20	30	30	0.038	0.110	0.027	7	3
18	16	30	0.048	0.110	0.027	10	5
16	26	30	0.061	0.123	0.027	14	8
14	41	30	0.074	0.142	0.027	20	13
14	19	26.5	0.071	0.134	0.027	19	13
12	65	30	0.086	0.158	0.027	29	20
10	105	30	0.119	0.194	0.027	44	32
10	19	23	0.115	0.186	0.027	43	32

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com

