

UL Style 1275

Appliance Wiring

105°C – 600 volts AC- Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
 Insulation: 105°C PVC
 RoHS and REACH Compliant

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors for base and stripe combinations
 Packaging options: reels, drums, returnable containers

Compliances

CSA AWM FT1
 Voltage Rating 600 volts AC
 Horizontal Flame per UL 1581
 UL 758
 60°C wet, Optional 60 or 80°C Oil Resistant

Applications

Internal wiring of Refrigerating Equipment

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
18	16	30	0.048	0.183	0.054	18	5
16	26	30	0.061	0.198	0.054	23	8
10	105	30	0.115	0.251	0.054	56	32

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com

