



UL Style 3321 XF OR XFF Appliance Wiring

150°C - 600 volts AC 750 volts DC - Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
 Insulation: 150°C XLPE
 RoHS and REACH Compliant

Compliances

CSA CL-1503
 Voltage Rating 600 volts AC 750 volts DC
 Horizontal Flame per UL 1581
 UL 758

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors for base and stripe combinations
 Packaging options: reels, drums, returnable containers

Applications

Internal wiring of appliances

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
18	16	30	0.048	0.113	0.027	10	5
18	7	26.5	0.046	0.108	0.027	9	5
16	26	30	0.060	0.120	0.027	14	8
16	7	24.5	0.059	0.120	0.027	13	8
14	41	30	0.074	0.144	0.027	20	13
14	7	22.5	0.072	0.138	0.027	20	14

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com

