



# UL Style 3049 Appliance Wiring

90°C - 600 volts AC - Horizontal Flame

### Features

Conductors available in solid or stranded, tinned or copper  
Insulation: 90°C Neoprene  
RoHS and REACH Compliant

### Product Design Options

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors for base and stripe combinations  
Packaging options: reels, drums, returnable containers

### Compliances

CSA AWM  
Voltage Rating 600 volts AC  
Horizontal Flame per UL 1581  
UL 758  
Oil Resistant 60°C

### Applications

Internal wiring of appliances

<b>AWG size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (In)</b>	<b>Nom OD (In)</b>	<b>Min Wall (In)</b>	<b>Approx. Net Weight (lbs/mft)</b>	<b>Approx. Cu (lbs/mft)</b>
1/0	1064	30	0.405	0.624	0.072	451	328

### Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.Prestolitewire.com](http://www.Prestolitewire.com)

Email: [bulkwiresales@prestolitewire.com](mailto:bulkwiresales@prestolitewire.com)



REV: -O-