



UL Style 3199 Appliance Wiring

105°C - 300 volts AC - Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
Insulation: 105°C XLPE
RoHS and REACH Compliant

Compliances

CSA 1054
Voltage Rating 300 volts AC
Horizontal Flame per UL 1581
UL 758

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels, drums, returnable containers

Applications

In appliances or as ballast leads for indoor
Use only.

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
18	19	30.5	0.045	0.082	0.013	7	5
16	26	30	0.060	0.096	0.013	11	8
20	10	30	0.038	0.075	0.013	5	3
22	7	30	0.030	0.065	0.013	4	2

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com



REV: -O-