

UL Style 3266 Appliance Wiring

125°C - 300 volts AC - Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
 Insulation: 125°C XLPE
 RoHS and REACH Compliant

Compliances

CSA AWM
 Voltage Rating 300 volts AC
 Horizontal Flame per UL 1581
 UL 758

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors for base and stripe combinations
 Packaging options: reels, drums, returnable containers

Applications

Internal Wiring of appliances

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
22	7	30	0.030	0.065	0.013	2	2
20	10	30	0.038	0.073	0.013	5	3
18	19	30.5	0.045	0.08	0.013	7	5
16	26	30	0.060	0.096	0.013	11	8
14	41	30	0.074	0.111	0.013	17	13
12	65	30	0.086	0.129	0.013	25	20
10	65	28	0.113	0.149	0.013	38	33

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com



Rev: -0-