



PW ES-1573
Prestoflex Welding Cable
125°C EPDM

Features

Conductors available in tinned or copper
Insulation: 125°C EPDM
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors
Packaging options: reels

Applications

Cables used for welding electrical

<i>AWG size</i>	<i>Number of Strands</i>	<i>Strand Size (ga)</i>	<i>Nom Cond OD (in)</i>	<i>Nom OD (in)</i>	<i>Min Avg Wall (in)</i>	<i>Approx. Net Weight (lbs/mft)</i>	<i>Approx. Cu (lbs/mft)</i>
6	280	30	0.185	0.356	0.056	127	80
4	440	30	0.237	0.403	0.056	183	128
1	880	30	0.345	0.485	0.063	340	258
2	704	30	0.297	0.529	0.067	268	192
1/0	1112	30	0.38	0.591	0.074	432	324
2/0	1408	30	0.429	0.635	0.074	520	409
3/0	1760	30	0.465	0.685	0.074	646	518
4/0	2224	30	0.544	0.764	0.081	810	653

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.prestolitewire.com