



# Standard Welding Cable

125°C EPDM

### Features

Conductors available in tinned or copper  
Insulation: 125°C EPDM  
RoHS and REACH Compliant

### Product Design Options

Custom strand constructions  
Custom diameter to meet design criteria  
Various colors  
Packaging options: reels

### Applications

Cables used for welding electrical

<b>AWG size</b>	<b>Number of Strands</b>	<b>Strand Size (ga)</b>	<b>Nom Cond OD (in)</b>	<b>Nom OD (in)</b>	<b>Min Avg Wall (in)</b>	<b>Approx. Net Weight (lbs/mft)</b>	<b>Approx. Cu (lbs/mft)</b>
6	266	30	0.194	0.323	0.042	111	79
4	392	30	0.211	0.375	0.046	164	115
3	525	30	0.248	0.377	0.042	196	154
2	672	30	0.284	0.424	0.046	248	197
1	779	30	0.346	0.51	0.056	315	243
1/0	1026	30	0.391	0.561	0.056	403	320
2/0	1130	30	0.434	0.606	0.056	482	390
3/0	1672	30	0.442	0.619	0.056	587	491
4/0	2052	30	0.547	0.728	0.056	721	602

### **Customer Service Group**

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.prestolitewire.com](http://www.prestolitewire.com)